



Model	SYNC-X7-I10S1T4	SYNC-X7-I10S3T4	SYNC-X7-I10S5T4	SYNC-X7-I10S1T5	SYNC-X7-I10S3T5	SYNC-X7-I10S5T5
Structure Size	4 Feet x 4 Feet			5 Feet x 5 Feet		
Material	Mild Steel Structure					
Chequered Plate Thickness	4.5mm					
U-Channel Design	Single (H)		Double (HH)	Single (H)		Double (HH)
U-Channel Material/Size	Mild Steel 2½ x 5					
Max. Capacity	1 tonne	3 tonnes	5 tonnes	1 tonne	3 tonnes	5 tonnes
Division	1/2kg	1kg	2kg	1/2kg	1kg	2kg
Elec. Indicator Model	SYNC-X7-I10S					
Elec. Indicator Material	Stainless Steel Housing					
Elec. Indicator Application	Weighing					
Load Cell Model	SYNC-X7-H8C					
Load Cell Capacity	4klb					

X7-I10S Weighing Indicator

Features:

- ✓ 40 x 112mm height liquid crystal display with backlight
- ✓ Multicolour LCD display
- ✓ Navigation keypad for intuitive menu use
- ✓ Programable to g, kg, lb or oz weighing units
- ✓ Unit change feature between metric and imperial units
- ✓ Single range or Multi range operation
- ✓ Linearity correction
- ✓ Remote weight indicator operation
- ✓ Check weighing function for Hi/OK/Lo with optical and acoustic announcement
- ✓ Piece counting function in high accuracy
- ✓ 100 products memory for check weighing
- ✓ 100 memory for checking the quantity at piece counting
- ✓ 100 products memory for piece counting
- ✓ Accurate animal weighing with dynamic load weighing algorithm
- ✓ Total memory at weighing and at counting
- ✓ Automatic power off function
- ✓ Multilanguage RS 232C data output for printer, PC or remote display connection
- ✓ 12 VDC or 100-240 VAC, 50-60 Hz
- ✓ Optional second RS-232C data output (PC and printer)

