



Mild-Steel Structure



Stainless Steel Structure

MS Model	SYNC-X7-I10S150M	SYNC-X7-I10S300M	SYNC-X7-I10S500M
Structure Material	Mild Steel Structure with Stainless Steel Cover		
SS Model	SYNC-X7-I10S150S	SYNC-X7-I10S300S	SYNC-X7-I10S500S
Structure Material	Stainless Steel Structure with Stainless Steel Cover		
Capacity	150kg	300kg	500kg
Division	50g	100g	200g
Structure Size	400mm x 500mm	500mm x 600mm	600mm x 800mm
Load Cell Model	SYNC-X7-L6E3200	SYNC-X7-L6G500	SYNC-X7-L6G750
Max. Capacity	200kg	500kg	750kg
Elec. Indicator Model	SYNC-X7-I10S		
Elec. Indicator Material	Stainless Steel Housing		
Elec. Indicator Application	Weighing		

## X7-I10S Weighing Indicator

### Features:

- ✓ 40 x 112mm height liquid crystal display with backlight
- ✓ Multicolour LCD display
- ✓ Navigation keypad for intuitive menu use
- ✓ Programable to g, kg, lb or oz weighing units
- ✓ Unit change feature between metric and imperial units
- ✓ Single range or Multi range operation
- ✓ Linearity correction
- ✓ Remote weight indicator operation
- ✓ Check weighing function for Hi/OK/Lo with optical and acoustic announcement
- ✓ Piece counting function in high accuracy
- ✓ 100 products memory for check weighing
- ✓ 100 memory for checking the quantity at piece counting
- ✓ 100 products memory for piece counting
- ✓ Accurate animal weighing with dynamic load weighing algorithm
- ✓ Total memory at weighing and at counting
- ✓ Automatic power off function
- ✓ Multilanguage RS 232C data output for printer, PC or remote display connection
- ✓ 12 VDC or 100-240 VAC, 50-60 Hz
- ✓ Optional second RS-232C data output (PC and printer)

