



Mild-Steel Structure



Stainless Steel Structure

MS Model	SYNC-X7-X2150M	SYNC-X7-X2300M	SYNC-X7-X2500M
Structure Material	Mild Steel Structure with Stainless Steel Cover		
SS Model	SYNC-X7-X2150S	SYNC-X7-X2300S	SYNC-X7-X2500S
Structure Material	Stainless Steel Structure with Stainless Steel Cover		
Capacity	150kg	300kg	500kg
Division	50g	100g	200g
Structure Size	400mm x 500mm	500mm x 600mm	600mm x 800mm
Load Cell Model	SYNC-X7-L6E3200	SYNC-X7-L6G500	SYNC-X7-L6G750
Max. Capacity	200kg	500kg	750kg
Elec. Indicator Model	SYNC-X7-X2		
Elec. Indicator Material	ABS Plastic Housing		
Elec. Indicator Application	Weighing		

X7-X2 Weighing Indicator

Features:

- ✓ ABS material housing
- ✓ Zero, tear, accumulating function
- ✓ Stable, Hi-OH-Lo, Low Power indication
- ✓ Overweight indication (Upper and lower limit)
- ✓ AC 220V / 50Hz or Rechargeable Battery 6V4.5AH
- ✓ Accuracy 1/30,000
- ✓ A/D Resolution Seven hundred thousand
- ✓ LED Display with backlight
- ✓ Programmable to units of g, kg, lb, oz
- ✓ The volume of the alarm light can be up to 120Db
- ✓ The volume of the alarm light can be adjusted
- ✓ Zero costs for the alarm light, save costs
- ✓ High precision open
- ✓ Can match with variety of platform scale & floor scale in market
- ✓ Counting function by auto or manual
- ✓ Automatically weighing within 3 seconds
- ✓ Animal function
- ✓ RS232 communication port
- ✓ Wi-Fi Module (Optional), USB Module (Optional), Print Function Module (Optional), Relay Set-Point (Optional)

