



SIRIM Pattern Approval No. Kelulusan : ATS-0053-20 / ATS-0054-20

Model : SYNC-X7-X7PC



Note: Illustrations are for reference only

Product Specification:

Model	SYNC-X7-X7PC
Brand	Synctronix
Input Sensitivity	0.2 Microvolts/degrees
Input Voltage Range	-2mv ~ 20mv
Loadcell Voltage	DC 5V, can match 4 loadcell
A/D Resolution	Seven Hundred Thousand
Input Impedance	> 1GΩ
A/D Transfer	10 times/second
Non-Linearity	≤ 0.01% F. S
Power Supply	AC 220V/50HZ Rechargeable Battery 6V/4.5AH
Display Mode	LCD Display with Green Backlight
Products Size	266 x 160 x 111.5 mm
Units	g, kg, lb, oz, tl
Working Temperature	-10 ~ +40°C (14 ~ 104°F)
Net Weight	2.53kg
Material	ABS Material Housing
Class	III
Interface	RS232, Wi-Fi Module (Optional), USB Module (Optional), Print Function Module (Optional)
Industry	Industrial & Commercial
SIRIM Pattern Approval	Yes

Product Features:

- ABS material housing
- Zero, tear, accumulating, counting, Hi-OK-Lo function
- Low power, overweight indication (Upper and lower limit)
- LCD display with black text and green backlight
- Standard built-in red, yellow and green alarm lights
- Upper and lower limit alarm function of Weight/Quantity
- RS232 communication port
- Optional: Wi-Fi Module, USB Module, Print Function Module
- Large screen display with big and clear fonts
- Adjustable volume of the alarm light up to 120Db
- High precision permission opening, self-adjustable value of capacity and division
- Can match with variety of platform scale & floor scale in market
- The angle of indicator can be adjusted



Company Address:

No. 34, Jalan Bagan 1, Taman Bagan,
13400 Butterworth, Penang, Malaysia.

Tel: +604-323 5822 | +6012-413 5822

Email: admin@synctronix.com.my

Website: www.synctronix.com.my

