



Model	SYNC-X7-X7221T4	SYNC-X7-X7223T4	SYNC-X7-X7225T4	SYNC-X7-X7221T5	SYNC-X7-X7223T5	SYNC-X7-X7225T5
Structure Size	4 Feet x 4 Feet			5 Feet x 5 Feet		
Material	Mild Steel Structure					
Chequered Plate Thickness	4.5mm					
U-Channel Design	Single (H)		Double (HH)	Single (H)		Double (HH)
U-Channel Material/Size	Mild Steel 2½ x 5					
Max. Capacity	1 tonne	3 tonnes	5 tonnes	1 tonne	3 tonnes	5 tonnes
Division	1/2kg	1kg	2kg	1/2kg	1kg	2kg
Elec. Indicator Model	SYNC-X7-X722					
Elec. Indicator Material	ABS Housing					
Elec. Indicator Application	Weighing					
Load Cell Model	SYNC-X7-H8C					
Load Cell Capacity	4klb					

X7-X722 Weighing Indicator

Features:

- ✓ Easy to handle plastic enclosure design
- ✓ Rugged ABS material housing
- ✓ Transparent dust-cover included
- ✓ Big LCD with backlit
- ✓ Accumulation
- ✓ Auto power off
- ✓ Low battery indication
- ✓ Support one analogue load cell platform with up to four 350Ω load cells
- ✓ Powered by either AC 100V ~240V/50Hz~60Hz and DC 9 V/1A or internal 6V4AH battery pack
- ✓ One standard serial port (COM1) as RS232 and DB9 serial port
- ✓ Front panel key access to basic weighing functions, Zero, Tare, Clear, configurable function, count and print
- ✓ Animal weighing: Peak hold, Data hold, Auto hold



Company Address:
No. 34, Jalan Bagan 1, Taman Bagan,
13400 Butterworth, Penang, Malaysia.
Tel: +604-323 5822 | +6012-413 5822
Email: admin@synctronix.com.my
Website: www.synctronix.com.my