



Mild-Steel Structure



Stainless Steel Structure

MS Model	SYNC-X7-X722150M	SYNC-X7-X722300M	SYNC-X7-X722500M
Structure Material	Mild Steel Structure with Stainless Steel Cover		
SS Model	SYNC-X7-X722150S	SYNC-X7-X722300S	SYNC-X7-X722500S
Structure Material	Stainless Steel Structure with Stainless Steel Cover		
Capacity	150kg	300kg	500kg
Division	50g	100g	200g
Structure Size	400mm x 500mm	500mm x 600mm	600mm x 800mm
Load Cell Model	SYNC-X7-L6E3200	SYNC-X7-L6G500	SYNC-X7-L6G750
Max. Capacity	200kg	500kg	750kg
Elec. Indicator Model	SYNC-X7-X722		
Elec. Indicator Material	ABS Plastics Housing		
Elec. Indicator Application	Weighing		

0

X7-X722 Weighing Indicator

Features:

- ✓ Easy to handle plastic enclosure design
- ✓ Rugged ABS material housing
- ✓ Transparent dust-cover included
- ✓ Big LCD with backlit
- ✓ Accumulation
- ✓ Auto power off
- ✓ Low battery indication
- ✓ Support one analogue load cell platform with up to four 350Ω load cells
- ✓ Powered by either AC 100V ~240V/50Hz~60Hz and DC 9 V/1A or internal 6V4AH battery pack
- ✓ One standard serial port (COM1) as RS232 and DB9 serial port
- ✓ Front panel key access to basic weighing functions, Zero, Tare, Clear, configurable function, count and print
- ✓ Animal weighing: Peak hold, Data hold, Auto hold

