



SIRIM Pattern Approval No. Kelulusan : ATS-0053-20 / ATS-0054-20

Model : SYNC-X7-X2



Product Specification:

Model	SYNC-X7-X2
Brand	Synctronix
A/D	Δ - Σ
Accuracy	1/30,000
Input Sensitivity	0.2 μ V/d
Input Voltage Range	-2mV ~ 20mV
Loadcell Voltage	DC 5V (can match 4 loadcell)
A/D Resolution	Seven Hundred Thousand (700,000)
Input Impedance	> 1G Ω
A/D Transfer	10 times/second
Non-Linearity	\leq 0.01% F.S.
Power Supply	AC 220V / 50Hz or Rechargeable Battery 6V4.5AH
Display Mode	LED Display with Backlight
Units	g, kg, lb, oz
Working Temperature Range	-10 $^{\circ}$ C ~ +40 $^{\circ}$ C (14 ~ 104F)
Dimension	266 x 160 x 111.5 mm
Weight	2.53kg
Material	ABS Material Housing
Class	III
Interface	RS232, Wi-Fi (Optional), USB (Optional), Print Module (Optional), Relay Set-Point (Optional)
Industry	Industrial & Commercial

Product Features:

- ABS material housing
- Zero, tear, accumulating, Hi-OK-Lo function
- Stable, low power, Overweight indication (Upper and lower limit)
- AC 220V 50Hz / Rechargeable Battery 6V4.5AH
- Accuracy 1/30,000
- A/D Resolution Seven hundred thousand
- LED Display with backlight
- Programmable to units of g, kg, lb, oz
- RS232 communication port
- Optional: Wi-Fi Module, USB Module, Print Module, Relay Set-Point Module
- The volume of the alarm light can be up to 120Db
- The volume of the alarm light can be adjusted
- Zero costs for the alarm light, save costs
- High precision open
- Can match with variety of platform scale & floor scale in market
- Counting function by auto or manual
- Automatically weighing within 3 seconds
- Animal function



Company Address:

No. 34, Jalan Bagan 1, Taman Bagan,

13400 Butterworth, Penang, Malaysia.

Tel: +604-323 5822 | +6012-413 5822

Email: admin@synctronix.com.my

Website: www.synctronix.com.my