



Model	SYNC-X7-X21T4	SYNC-X7-X23T4	SYNC-X7-X25T4	SYNC-X7-X21T5	SYNC-X7-X23T5	SYNC-X7-X25T5
Structure Size	4 Feet x 4 Feet			5 Feet x 5 Feet		
Material	Mild Steel Structure					
Chequered Plate Thickness	4.5mm					
U-Channel Design	Single (H)		Double (HH)	Single (H)		Double (HH)
U-Channel Material/Size	Mild Steel 2½ x 5					
Max. Capacity	1 tonne	3 tonnes	5 tonnes	1 tonne	3 tonnes	5 tonnes
Division	1/2kg	1kg	2kg	1/2kg	1kg	2kg
Elec. Indicator Model	SYNC-X7-X2					
Elec. Indicator Material	ABS Housing					
Elec. Indicator Application	Weighing					
Load Cell Model	SYNC-X7-H8C					
Load Cell Capacity	4klb					

X7-X2 Weighing Indicator

Features:

- ✓ ABS material housing
- ✓ Zero, tear, accumulating function
- ✓ Stable, Hi-OH-Lo, Low Power indication
- ✓ Overweight indication (Upper and lower limit)
- ✓ AC 220V / 50Hz or Rechargeable Battery 6V4.5AH
- ✓ Accuracy 1/30,000
- ✓ A/D Resolution Seven hundred thousand
- ✓ LED Display with backlight
- ✓ Programmable to units of g, kg, lb, oz
- ✓ The volume of the alarm light can be up to 120Db
- ✓ The volume of the alarm light can be adjusted
- ✓ Zero costs for the alarm light, save costs
- ✓ High precision open
- ✓ Can match with variety of platform scale & floor scale in market
- ✓ Counting function by auto or manual
- ✓ Automatically weighing within 3 seconds
- ✓ Animal function
- ✓ RS232 communication port
- ✓ Wi-Fi Module (Optional), USB Module (Optional), Print Function Module (Optional), Relay Set-Point (Optional)

